

TOTO®

ABA789L/ABA789R Clayton™ 66" x 36" Air Bath™

TOTO® USA, INC. has merged heated air and water to create the ultimate in bathing luxury:

The TOTO® Clayton™ Air Bath™

The TOTO® Clayton™ Air Bath™ will provide the bather a soothing, relaxing and refreshing repose uniquely different than any other bath-time experience. The cast-acrylic Clayton™ Air Bath™ has smooth lines and a deep bathing well which is accented with a chrome plated solid brass grab bar and 12 individual air jets. The individualized check valve system allows the bather to use soaps, bath oils, salts and other bathing essentials without harming the performance of the air system.



ABA789R - Clayton™ 66" x 36" Air Bath™

- 66" x 36" x 21-3/8"
- Luxuriously deep Bathing Well
- Cast-acrylic construction provides years of durability
- Slip-resistant surface
- 1 hp Ultra-quiet Blower
- 300 watt Heated Air Injection System
- Final purge/drying cycle to clean each air jet
- Chrome Plated Solid Brass Grab Bar

- Multi functional Keypad
 - Normal Mode -**
5 Intensity Levels For Continuous Operation
 - Pulsating Mode -**
Alternating between the High/Low Intensity levels for Massage
 - Oscillation Mode -**
Alternating between all 5 Intensity levels for Massage

- **ABA789L**
Acrylic bathtub. Slip-resistant surface. Left keypad/ right blower

- **ABA789R**
Acrylic bathtub. Slip-resistant surface. Right keypad/ left blower

Colors:

Standard #01 Cotton
#12 Sedona Beige

Optional See price book for additional colors

Grab Bar Chrome

Jet Trim Chrome
#01 Color Matched

ABA789L/ABA789R

Clayton™ 66" x 36" Air Bath™

■ STYLE

Designed to match our line of residential bathroom products, TOTO's® tubs complete any bathroom suite. Lucite cast acrylic construction provides the ultimate in strength and durability, while a slip-resistant surface enhances safety in the bath.

■ SPECIFICATIONS


Size: 66"L x 36"W
 Depth: 21-3/8"
 Warranty: 5 Year Limited Warranty on Acrylic Tub
 1 Year Limited Warranty on Components and Parts
 Material: Lucite Cast Acrylic

Electrical Requirements:
 15 AMP; 120V w/GFI

Shipping Weight:
ABA789L/ABA789R
 120 lbs.

Shipping Dimensions:
ABA789L/ABA789R
 67-1/4"L x 38-1/4"W
 x 26"H

Gallons: **ABA789L/ABA789R**
 85 to overflow



ABA789R - Clayton™ 66" x 36" Air Bath™



Fixture meets ANSI/ASME standard Z124.1, ETL, and C-UPC requirements.

These dimensions and specifications are subject to change without notice.

Use TOTO® cut template to assure rough in dimensions.

TOTO®

TOTO U.S.A., INC. • 1155 Southern Road, Morrow, GA 30260
 Tel. (888) 295-8134 • Fax. (800) 699-4889 • www.totousa.com

Printed in U.S.A. © TOTO LTD. 02/06 #DXXXXXX

Printed on recycled paper

REV 02/06